



WEVER & DUCRÉ
LIGHTING

STAKE FOLD 1.0

727274D5

Project

Type

Notes

Quantity

Date

GENERAL

Floor
Projector
Dark Grey Texture
IP65
Exterior
460 lm

LED

3000 K
CRI 90
L95 / 50000 h
3-step binning
MR 0.59
MDER 0.54

OPTICAL

Wide Flood

PHYSICAL


Length 80 mm
Width 100 mm
Height 32 mm
0.78 kg
Tilt max 90°

ELECTRICAL


phase-cut dim
220 - 240 V
Total connected power 8 W
PC1
Safety distance 0.3 m



IP65 $\pm 0,3 \rightarrow D$



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

STAKE FOLD 1.0

727274D5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.98	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Snoot

TYPE	L · W · H (MM)	ORDERCODE
STAKE STAKE FOLD	75-30-39	9 0 0 1 9 0 0 4

GROUND SPIKE

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
STAKE POLE FOLD	70-70-354	9 0 0 1 3 1 0 7