

# FLOS

09.5045.30BDA White

## Super Flat Suspension 120x30 Up&Down Dali Version


Designed by FLOS Architectural, 2018



General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Suspension
Environments	Indoor dry location
LED type	Top LED
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	56
Source flux (lm)	5429,31
System flux (lm)	4225

### Physical

Colour	White
Trim	No
Orientation	Fixed
Net weight (kg)	4.20
IP internal	20
IP external	20

### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  LDT


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



## Schematic light drawing



### Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	109
Beam angle C90-270 (°)	91

### Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	35.00
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable DALI 1
Emergency type	No

### Notes

Total consumption of the system: 56W. Light source: Up: max. 3482 lm. Down: max. 3482 lm. Luminous efficiency of luminaire: max. 138 lm/W.