

TEMPO

Design by Liovore Altherr.

Reference

5764.

Application

Wall Lamps

Installation type

Surface

Description

Wall lamp composed of a stylized profile attached to the wall and topped by a blown glass diffuser that gives the piece a delicate image. Connection with plug. LED light source.

Diffuser

Blow-glass diffuser

Materials

Body: Steel

Diffuser: Blown-glass

Finish



5764-18 Matt graphite lacquer (ADAPTA RF 9913 WX)



5764-35 Matt brick lacquer (NCS S 4040-Y70R)




5764-58 Matt cream lacquer (RAL 7044)



5764-62 Matt green lacquer (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA



Led 2700K CRI >90 550 lm 137 lm/W

Driver included: CC - Constant Current 350 mA 220-240V 50/60Hz

Electronic dimming PUSH

Technical characteristics

- Push button on base dimming

Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0551 m³ /

Gross weight 3.5 kg. / Net weight 1.7 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Certificates



