

FLOS

03.6610.3C White/Aluminium

Light Supply Fixed Trim

Designed by FLOS Architectural, 2014

LED - Phosphor LED - 28W - 1696lm - 4000K - CRI> 80 - Beam° 49



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	Phosphor LED
Lamp category	LED
Iicos	No
Number of heads	1
Power (W)	28
Source flux (lm)	2872
System flux (lm)	1696

Physical

Colour	White/Aluminium
Trim	No
Orientation	Fixed
Recessed depth (mm)	277
Net weight (kg)	0.98
IP internal	20
IP external	44



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Beam Angle: 49°

h(m)	E(lx)	D(m)
1	3265	0.91
2	816	1.81
3	363	2.72
4	204	3.62
5	131	4.53

Luminous flux luminaire
2270 lm (EXTREME CUT OFF)

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	49
Beam angle C90-270 (°)	49

Electrical

Insulation class	II
Frequency (Hz)	50/60
Driver	Remote included
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No