



SPINEO

CEILING RECESSED



p. 587



1.0 LED

LED AC MOD 8W | 220-240V
COB 3-step | incl. PS | phase cut dim
aluminium powder coated

0.20kg IP20 0.3-1 36°

80 28°/28° 355° 70 4-18

wire springs

| | CODE |
|--|----------|
| | 160168W_ |
| | 160168B_ |

blade springs

| | CODE |
|--|-----------|
| | 160168W_C |
| | 160168B_C |

Light Colour Selection

| | LUMEN | CRI | CODE |
|-------|-------|-----|------|
| 2700K | 480 | >90 | 3 |
| 3000K | 500 | >90 | 5 |

fits into Kaiser ThermoX® 9320-21



1.0 MR16

QR-CBC51 max.35W | GU5.3
12V | excl. power supply
aluminium powder coated
matt chrome

0.14kg IP20 0.9-1

80 35°/35° 355° 70 4-18

wire springs

| | CODE |
|--|----------|
| | 160110W0 |
| | 160110B0 |

blade springs

| | CODE |
|--|-----------|
| | 160110W0C |
| | 160110B0C |

ALWAYS USE

| | CODE |
|---------------|----------|
| power supply | |
| 12V 10W dim | 90221401 |
| 12V 25W dim | 90221701 |
| 12V 70W dim | 90221904 |

more specs on page 591

fits into Kaiser ThermoX® 9320-21



1.0 PAR16

PAR16 max.12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated
matt chrome

0.18kg IP20 0.9-1

80 35°/35° 355° 70 4-18

wire springs

| | CODE |
|--|----------|
| | 160120W0 |
| | 160120B0 |

blade springs

| | CODE |
|--|-----------|
| | 160120W0C |
| | 160120B0C |

OPTIONAL

| | CODE |
|------------------------------------|----------|
| PAR16 LED GU10 7W phase-cut dim | |
| 2700K | 901228W2 |
| 3000K | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 593

fits into Kaiser ThermoX® 9320-21