

**WINK ASY 82 LED SPREADLIGHT GE**


Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable, so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon. With the debut of the Wink 82, we are also presenting a completely new Wink accessory: Wink flange. Compatible with all 3 Wink lamps, Wink flange adds an extra accent in the form of a low ring around the spot, rather than a completely seamless install. Its precision-designed conical shape complements the spot, enabling it to have a quiet conversation with the ceiling.

Art. Nr. 14202032

**SPECIFICATIONS**

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 98 h 100 (Wink Flange) or ø 111 h 100 (Recessed ring)	
Weight	0.29kg	
Min. distance	0.1 m	
IP	IP54	
Glow wire test	960°	
Lifetime	L80 B20 @ 50.000 hrs	
CRI	90	
Power supply	350mA	<b>500mA</b>
	17.8Vf	<b>18.4Vf</b>
Connected load	6.2W	<b>9.2W</b>
Lumen	317lm	<b>425lm</b>
Efficacy	51lm/W	<b>46lm/W</b>
UGR	28	<b>29</b>
Adjustability	h 360°	
Remark	! must be used with recessed ring or flange ! LED light is inserted at a 30° angle	

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
black struc	<b>14202032</b>	14202132
white struc	14202009	14202109



Available label  
<http://supemodular.com/assets/TYPE2.pdf>



## WINK ASY 82 LED SPREADLIGHT GE

### ACCESSORIES

#### HUE-BRIDGE

70000616	HUE BRIDGE EU
----------	---------------

#### HUE-DEVICE

70000152	HUE DIMMER SWITCH
----------	-------------------

70000615	HUE TAP SWITCH
----------	----------------

70008054	HUE SENSOR
----------	------------