



Eiffel Pendant

Designed by Krøyer Sætter Lassen



FRAMA

Eiffel Assembly Guide

Contents:

In this box you will find:

- 1 led tube bulbs
- 1 ceiling mounted Eiffel frame, with plated brass end details, black wire, eu plug
- 2 adjustable ceiling attachments
- 1 Allen Key for adjusting ceiling attachments

Assembly:


Start by unpacking the Eiffel Frame. After locating and marking the desired ceiling placement of the Eiffel lamp, locate fastening anchors at the ends of each wire cord. These will be drilled directly into the ceiling. Please note external wall anchors may be necessary depending on ceiling material.

Secondly, measure the height the eiffel fixture should be set from the ceiling. Using the allen key provided, adjust the anchors to allow the proper length of wire for desired height. After tightening the anchor so the wire is secure, begin drilling the anchor into the marked ceiling placement. Repeat on other side.

Holding the lamp secure, mount LED tube bulb within the bottom socket, from a 90° angle at the same time Never attempt to mount sockets one at a time. This may result in high risk of LED tube breaking.


After all parts are secure and mounted, turn off the power and wire in the Eiffel lamp. Should you like to dim the light, simply turn the brass cap on the left end of the piece to achieve desired light.

Contents:




Assembly:


1



2



3



To dim light fixture,
turn brass cap on
the base to achieve
desired light

Eiffel Maintenance Guide

Waxing Untreated Metal:

Should you want to add an additional protective layer to eiffel, follow the below instructions on waxing metal. Note this should not be applied to brass ends of the product. Take care when applying wax to avoid the inner socket areas.

Since wax is only a coating and doesn't actually bind with metals, it must be periodically reapplied. As long as the piece is indoors, the wax will typically last at least a few years.

1. Use mineral spirits to clean the steel before application.
2. Using warm, clear wax, rub a thin layer over the metal with a soft cloth.
3. Using a clean cloth, buff out all of this dull wax with circular motions.
4. When the wax has been sufficiently buffed, the dullness will be gone, replaced with a slight shine. The finished wax should feel smooth and slippery to the touch.

Eiffel Pendant 1000

Dimensions : H 45 L1000 D200

Eiffel Pendant 500

Dimensions : H 45 L500 D200

Materials : Black steel frame, plated brass end details, 16.5 W
led tube bulb, black silicon wire, eu plug

☞ Designed in Denmark | Produced in PRC

Eiffel Pendant 1000

Item No. 2105



Eiffel Pendant 500

Item No. 2106



FRAMA

Org. St. Pauls Apotek - Fredericiagade 57 - Copenhagen