

FLOS

09.5025.30B White

Super Flat Suspension 90x90 Up&Down No Dimmable


Designed by FLOS Architectural, 2018



General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Suspension
Environments	Indoor dry location
LED type	Top LED
Lamp category	LED
Iicos	No
Number of heads	1
Power (W)	55
Source flux (lm)	5429,31
System flux (lm)	4450

Physical

Colour	White
Trim	No
Orientation	Fixed
Net weight (kg)	8.30
IP internal	20
IP external	20

Download

[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  LDT


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	107

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	35.00
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Notes

Total consumption of the system: 55W. Light source: Up: max. 3482 lm. Down: max. 3482 lm. Luminous efficiency of luminaire: max. 138 lm/W.