

## DUELL WALL LED 900LM TRE DIM GI


With its gentle curves, Duell gives every room a softer touch. As a wall luminaire, Duell creates a wide fan of light on the wall, both upwards and downwards. The double-walled housing allows you to play with colour. On the outside, you'll enjoy extra choices of anodised black, bronze, silver bronze and champagne, while the inside is available in black, champagne and aluminium. In any of its colour choices, Duell will effortlessly give an architectural, high-end touch to your expression.

|                                           | WARM WHITE<br>2700K / CRI 90+ |
|-------------------------------------------|-------------------------------|
| ano black<br>(alu interior)               | 11074998                      |
| ano black<br>(black interior)             | 11074903                      |
| ano black<br>(champagne interior)         | 11074908                      |
| ano bronze<br>(alu interior)              | 11074999                      |
| ano bronze<br>(black interior)            | 11074910                      |
| ano bronze<br>(champagne interior)        | <b>11074911</b>               |
| ano champagne<br>(black interior)         | 11074996                      |
| ano champagne<br>(champagne interior)     | 11074997                      |
| ano silver bronze<br>(black interior)     | 11074912                      |
| ano silver bronze<br>(champagne interior) | 11074995                      |
| black struc<br>(gold interior)            | 11074991                      |
| white struc<br>(champagne interior)       | 11074939                      |

Art. Nr. 11074911

### SPECIFICATIONS

|                 |                      |
|-----------------|----------------------|
| Lamp            | 2x LED Array 5W      |
| Gear / Transfo  | LED gear incl.       |
| Weight          | 1.21kg               |
| Min. distance   | 0.1 m                |
| Power supply    | 230V                 |
| IP              | IP20                 |
| Glow wire test  | 960°                 |
| Lifetime        | L80 B20 @ 50.000 hrs |
| CRI             | 90                   |
| CIE flux code   | 68/93/99/50/59       |
| Luminaire power | 12W                  |
| Lumen           | 763 Lm               |
| Efficacy        | 64 Lm/W              |
| UGR             | 17                   |
| Adjustability   | Not Applicable       |



Available label  
<http://supemodular.com/assets/TYPE2.pdf>

