

THIMBLE 74 LED GE

Thimble evokes minimalism, surprise and technology all at once. Subtle curves, slightly revealing colours, high-quality lens and LED. With its deep-recessed and glare-free light source, Thimble's clean and seamless execution makes it a quiet yet sophisticated choice for high-end residential or hospitality settings. This versatile, elegant architectural downlighter will bring pure form, definition and quality light to any space without stealing all the attention.

Art. Nr. 11620182

SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 70 h 100	
Weight	0.25kg	
Min. distance	0.1 m	
IP	IP55	
Glow wire test	960°	
Lifetime	50000 hrs	
CRI	90	
Power supply	350mA	500mA
	16Vf	16.2Vf
Connected load	5.6W	8.1W
Lumen	487lm	671lm
Efficacy	87lm/W	83lm/W


UGR

Adjustability

Not Applicable

Available label
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
	MEDIUM 30°	MEDIUM 30°
ano black	11620081	11620181
ano bronze	11620082	11620182
ano champagne	11620041	11620141
ano gold	11620042	11620142
ano silver bronze	11620084	11620184
black struc	11620032	11620132
white struc	11620009	11620109



THIMBLE 74 LED GE

ACCESSORIES

CONBOX

11624130	CONBOX 140X400X100X210
11624030	CONBOX 140X250X100X210

