

FLOS

07.9641.14ADA Black

Light Bell Dali Version


Designed by Piero Lissoni, 2017



Suspended luminaire for mounting on the ceiling with LED light source. (4 metres maximum distance to ceiling). Power supply source integrated into luminaire housing. Reflector not included; supplied separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Suspension
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	55
Source flux (lm)	6388

Physical

Colour	Black
Trim	No
Orientation	Fixed
Cord length (mm)	4000
Net weight (kg)	3.81
IP internal	20

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	78
Beam angle C90-270 (°)	78

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable DALI 1
Emergency type	No

Notes

Pin-block type dissipater. Please ask us for a higher IP. Includes a 4-meter suspension cable.

Accessories & Power Supply



OPTIONAL
Accessory

07.9630.70

Light Bell



OPTIONAL
Accessory

07.9630.76

Light Bell



OPTIONAL
Accessory

07.9630.AN

Light Bell



OPTIONAL
Accessory

07.9630.AP


Light Bell



OPTIONAL
Accessory

07.9630.CE


Light Bell



OPTIONAL
Accessory

08.8775.40

Rosette. IP20



OPTIONAL
Accessory

08.8775.14

Rosette. IP20



OPTIONAL
Accessory

F0556020

Light Bell Canopy Power supply
for standard and dimmable
versions



OPTIONAL
Accessory

F0557020

Rosette for indoors. IP20.

Dimmable Push/Dali