

FLOS

03.6613.3B White/White

Light Supply Wall-Washer Trim

Designed by FLOS Architectural, 2015


LED - Phosphor LED - 28W - 1918lm - 4000K - CRI> 80 - Beam° 37



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	Phosphor LED
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	28
Source flux (lm)	2872
System flux (lm)	1918

Physical

Colour	White/White
Trim	No
Orientation	Fixed
Recessed depth (mm)	290
Net weight (kg)	1.01
IP internal	20
IP external	44

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Beam Angle:	37°	
h(m)	E(lx)	D(m)
1	2209	0.76
2	552	1.53
3	245	2.29
4	138	3.06
5	88	3.82

Luminous flux Luminaire
1918 lm (EXTREME CUT OFF)

Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	37
Beam angle C90-270 (°)	52

Electrical

Insulation class	II
Frequency (Hz)	50/60
Driver	Remote included
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No