



K72 IP54 LED TRE DIM RG

K already earned its spurs in the Modular range. With the LED dedicated rework of the K we honour an icon. A timeless product that will remain in the Modular portfolio for many years to come. Suitable for general and accent lighting, K is available in donkey grey and white structure.

Art. Nr. 14041032

SPECIFICATIONS

| | |
|----------------|--------------------|
| Lamp | 1x LED Array 9.2W |
| Gear / Transfo | LED gear incl. |
| Cut-out size | ø 65 h 60 |
| Weight | 0.29kg |
| Min. Distance | 0.1 |
| Power supply | 230V |
| IP | IP54 |
| Glow Wire Test | 960° |
| CRI | 90 |
| Lumen | 661 Lm |
| Efficacy | 55 Lm/W |
| UGR | 21 |
| Adjustability | Not Applicable |
| Remark | ! 3500K on request |

| | WARM WHITE 2700K / CRI 90+ | | | WARM WHITE 3000K / CRI 90+ | | | NEUTRAL WHITE 4000K / CRI 90+ | | |
|-------------------------|-------------------------------|---------------|--------------|-------------------------------|---------------|--------------|----------------------------------|---------------|--------------|
| | SPOT 15° | MEDIUM 25° | FLOOD 40° | SPOT 15° | MEDIUM 25° | FLOOD 40° | SPOT 15° | MEDIUM 25° | FLOOD 40° |
| donkey grey struc | 14041071 | 14041171 | 14041271 | 14041371 | 14041471 | 14041571 | 14041671 | 14041771 | 14041871 |
| white struc | 14041009 | 14041109 | 14041209 | 14041309 | 14041409 | 14041509 | 14041609 | 14041709 | 14041809 |



This label is available in other languages:
<http://supermodular.com/assets/TYPE2.pdf>

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

K72 IP54 LED TRE DIM RG

ACCESSORIES

CONBOX

| | |
|----------|------------------------|
| 10490330 | CONBOX 112X172X100X236 |
|----------|------------------------|