



Oblique Qi NEW

Designed by Vincent Van Duysen, 2020




LED - Top LED - 8W - 479lm - 2700K - CRI> 90 - Beam° 35

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Base with Qi compatible wireless recharging system for mobile devices and wireless recharging cases for compatible devices.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Table	
Enviroment	Indoor dry location	
LED type	Top LED	
Lamp category	LED	
Number of heads	1	
Power (W)	8	
System power (W)	28	
Source flux (lm)	754	
System flux (lm)	479	

Physical

Colour	Glossy Sage	
Orientation	Fixed	
Net weight (kg)	0.75	
IP	20	
IP external	20	

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D <u>↓</u> ZIP 3D <u>↓</u> ZIP









Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F

https://professional.flos.com/en/global/product/oblique-qi-09.8310.dv/

09.8310.DV

Schematic light drawing



Beam Angle:		35°
h(m)	E(lx)	D(m)
1	229	2.18
2	57	4.36
3	25	6.54
4	14	8.72
5	9	10.90

Luminous flux luminaire 479 lm

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	35
Beam angle C90-270 (°)	46

Electrical

Insulation class	III
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable
Emergency type	No
Induction recharge QI	Yes
Charging socket/connector	USB-C