


MÉDARD RECESSED 42 LED GE

Médard recessed broadens the variety of applications. In contrast to the rest of the family, Médard recessed's light source is fixed, emanating a medium or flood beam angle. Hospitality environments including wellness centers, and high-end residential spaces, including bathrooms, will be spot-on locations for this IP55-rated new family member.

Art. Nr. 11550109

SPECIFICATIONS

Lamp	1x LED Module	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 40 h 65	
Weight	0.11kg	
Min. distance	0.1 m	
IP	IP55	
Glow wire test	960°	
Lifetime	50000 hrs	
CRI	90	
CIE flux code	100/100/100/100/79	
Power supply	350mA	500mA
	8.5Vf	8.8Vf
Connected load	3W	4.3W
Lumen	272lm	366lm
Efficacy	91lm/W	85lm/W
UGR	14	15
Adjustability	Not Applicable	



Available label
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+		WARM WHITE 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°	MEDIUM 25°	FLOOD 40°
black struc	11550032	11550132	11550232	11550332
white struc	11550009	11550109	11550209	11550309



MÉDARD RECESSED 42 LED GE

ACCESSORIES

HUE-MODULE

13190130 | HUE DIM CIRCUIT MODULE 150-300W 0/1-10V

HUE-BRIDGE

70000616 | HUE BRIDGE EU

70000617 | HUE BRIDGE UK

HUE-DEVICE

70000615 | HUE TAP SWITCH

70000154 | NIKO PURE SWITCH FOR HUE - WHITE STEEL

70000155 | NIKO PURE SWITCH FOR HUE - BLACK STEEL

70000152 | HUE DIMMER SWITCH

70008054 | HUE SENSOR

